p09 E220 Transport Stretcher

Cogent's E220 Transport Stretcher equipped with tuck-away siderails. The streamlined design makes stretcher transport patients efficiently and speedily. The 700lbs weight capacity of stretcher can treat patients with different weights. It equipped with four-wheel brake and fifth wheel which offers excellent mobility to provide the best safety to patients.















■ Optional ■

Standard Features

- Integrated storage tray with oxygen tank through which is made with ABS plastic
- Foot pedal for hydraulic system control on both ends
- Structure with two-section
- Structure with four-section can do knee gatch which provides patients comfort
- Drainage Bag clasp x 2 & Urinary Bag clasp x 2
- Foot controlled brake / steer pedal for four wheels in two end of stretcher
- IV pole inserted hole x 5
- Dual pneumatic assisted backrest
- Two stages movable IV pole x 1
- Two stages permanent folding IV pole x 1
- Foot-end assist push bar
- Velcro tape underneath the mattress
- Protective corner bumpers x 4
- Hook / Jack for upright oxygen tank holder
- Retractable steering fifth wheel
- Integrated with conductive chain
- Tuck-away siderail (one-piece ABS)
- Cylinder sleeves (PP plastic)
- Head-end ergonomic push handles

Specifications

- Overall Length: 213 cm
- Overall Width: 81 cm
- Height Range (from ground to litter top)

High: 35'' (89 cm) ± 2

Low: 22'' (54 cm) ± 2

- Weight Capacity: 700 lbs (318 kg)
- Litter Positioning

Backrest: $0-90^{\circ} \pm 2^{\circ}$

Trend. / Reverse Trend.: $0-18^{\circ} \pm 2^{\circ}$

- Mattress Base: 76" x 26" (193 x 64cm) ± 2
- Mattress Dimension: 3''(8cm), $195 \times 68cm \pm 2$
- Siderail: 43" x13" (115 x33cm) ± 2
- Caster Diameter: 8" (20 cm)
- Manual Knee Gatch: 0- 40°± 2° (Optional)

- Two years warranty for stretcher under normal use after date of shipping
- Extended warranty available